

WELLMATE HP TANK SERIES SIZING CHART

Model	Capacity		Drawdown 30-50 Setting**		Max. Operating Pressure (Diameter		Height		Connection	Assembly Weight	
	Gallons	Liters	Gallons	Liters	psig	kPa / bar	inch	cm	inch	cm	Top / Bottom	lb	kg
HP-7	30	114	6.6	25	75	500 / 5.0	16	41	43.75	11	1/4" VENT LINE 1 1/4" SOCKET	26	11.8
HP-9	40	151	9	34.1	75	500 / 5.0	16	41	56.5	144	1/4" VENT LINE 1 1/4" SOCKET	29	13.2
HP-85SQ	40	151	8	30.3	75	500 / 5.0	21	53	35.25	90	1/4" VENT LINE 1 1/4" SOCKET	34	15.4
HP-18	80	303	17.8	67.4	75	500 / 5.0	21	53	62	157	1/4" VENT LINE 1 1/4" SOCKET	44	20
HP-26	120	454	25.5	96.5	75	500 / 5.0	24	61	72.5	184	1/4" VENT LINE 1 1/4" SOCKET	64	29

**In keeping with current industry standards, drawdown factors are based on Boyle's law. Actual drawdowns will vary depending upon system variables, including the accuracy and operation of the pressure switch and gauge, actual percentage pressure, and operating temperature of the system.

Notes:

All tanks may be used up to 100°F (38°C) maximum internal water temperature and 120°F (50°C) external temperature.