

WATER SOFTENER SIZING CHART

Description	Cubic Feet	Media Tank	Brine Tank / Cabinet Size	Salt Storage Capacity	Service Flow Rate	Flow Rate		Backwash USGPM	Weight	Inlet/Outlet Connection
						@ 15psi Pressure Drop	@ 25psi Pressure Drop			
HEDP SERIES										
SOFTENER 485HEDP-100	1.0'	9" x 48"	20.3" x 37.4"	350 lbs	N/A	7.2 gpm	10.0 gpm	2.0 gpm	184 lbs	
SOFTENER 485HEDP-150	1.5'	10" x 54"	23.0" x 40.5"	420 lbs	N/A	7.4 gpm	10.1 gpm	2.4 gpm	201 lbs	
SOFTENER 485HEDP-200	2.0'	12" x 52"	23.0" x 40.5"	420 lbs	N/A	9.0 gpm	11.9 gpm	3.5 gpm	244 lbs	
SOFTENER 485HEDP-250	2.5'	13" x 54"	23.0" x 40.5"	420 lbs	N/A	9.2 gpm	12.1 gpm	4.0 gpm	262 lbs	
Electrical Requirements: Input 120V 60 Hz, Output 12V 650mA										
Water Temperature: 39°F to 100°F (4° to 38°C)										
Water Pressure: 20 - 125 psi										